

QUIET STATEMENT

Arabesque / Kasbah / Maroc / Medina



Construction	Tufted, Textured Loop Pile
Face Fibre	ECONYL® 100% recycled Nylon
Stain Resistance	StainSmart® for stain resist and soil release
Finished Face Weight	590 g/m ²
Gauge	47.2 / 10 cm
Rows	42.0 / 10 cm
Tuft Density	198,425 /m ²
Finished Pile Height	3.4 mm
Standard Backing	WellBAC® Comfort Plus 95% recycled open cell polyurethane cushion backing. Available with TractionBack® on request
Nominal Total Thickness	10.2 mm
Tile Size	50 cm x 50 cm
Nominal Total Weight	4300 g/m ²
Tiles per Box	18 (4.5m ²)

PERFORMANCE

Flammability (Euroclassification EN13501:1-2018)	Class Cfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Castor Chair (BS EN 985:2001)	Class A - Intensive use (r value ≥ 2.4)
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	31 dB ΔL _w
Sound Absorption (ISO354)	0.30 Class D
Alpha p values	125Hz 0.00, 250Hz 0.10, 500Hz 0.35, 1000Hz 0.20, 2000Hz 0.25, 4000Hz 0.40

ENVIRONMENTAL

72% recycled content by total product weight

Manufactured in location certified to: ISO9001:2015 / ISO14001 / ISO45001 / ISO50001 using renewable electricity

M/PACT™ Carbon Offset Floors, 4.88 kg CO₂ e/m² Embodied Carbon (EPD calculation A1-A3) Cradle to Gate footprint 100% off set

WARRANTIES

15 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICATIONS

INSTALLATION



CE

--	--	--	--	--	--	--